

ACLARACIÓN N° 3

LICITACIÓN PÚBLICA “SOLUCION SEGURIDAD INTEGRACION LINEAS 6 Y 3”

1. Modifica Cronograma Artículo 1 Cronograma, de acuerdo a lo siguiente:

RECEPCIÓN DE OFERTAS

DÍA : 24.05.2017

HORARIO : Hasta las 13:00 hrs.

LUGAR : Subgerencia de Abastecimiento, 2° piso Edificio CCA.

DIRECCIÓN : Av. Libertador Bernardo O’Higgins N° 1414, Santiago.

CONTACTO : Jeannette Peña

APERTURA DE OFERTAS TÉCNICAS

DÍA : 24.05.2017

HORA : 15:00 horas

LUGAR : Subgerencia de Abastecimiento, 2° piso Edificio CCA

2. Modifica REQ5. de las Especificaciones Técnicas

Donde dice:

Features	Next Generation Firewall
Stateful inspection firewall throughput	10 Gbps
Concurrent firewall connections	2.000.000
Firewall connections per second	125.000
Option for Security Contexts	Up to 250 (License required)
Authentication	Active Directory agent, LDAP, Kerberos, NTLM
3DES/AES IPsec VPN throughput	3 Gbps
Interfaces	16-port 10/100/1000, 4-port 10 Gigabit Ethernet (SFP+) 10 GbE license required
Management Ports	2-port 10/100/1000
Virtual interfaces (VLANs)	1024
High Availability	Active/active and Active/standby
Scalability	VPN clustering and load balancing
Redundant Power	Yes
Memory	24 GB

Tabla 1: Características de equipamiento de Seguridad Perimetral.

Debe decir:

Features	Next Generation Firewall
NGFW Throughput (FW + IPS + AVC)	4,75 Gbps
Maximum concurrent sessions (NGFW)	2.000.000
Maximum new connections per second (NGFW)	24.000
Application Visibility and Control	More than 4000 applications, Geolocations, Users, and Websites
Authentication	Active Directory agent, LDAP, Kerberos, NTLM
3DES/AES IPsec VPN throughput	3 Gbps
Interfaces	12 x 10M/100M/1GBASE-T Ethernet interfaces (RJ-45), 4 x 10 Gigabit (SFP+) Ethernet interfaces
Network Modules	8 x 10 Gigabit Ethernet (SFP+) network module
Management Ports	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)
Virtual interfaces (VLANs)	1024
High Availability	Active/Standby
Redundant Power	Single 400W AC, Dual 400W AC optional. Single/Dual 350W

Tabla 2.1: Características de equipamiento de Seguridad Perimetral.

Features	ASA Concentrador VPN
Typical use case	Datacenter
Stateful inspection firewall throughput (Maximum)	4 Gbps
Stateful inspection firewall throughput (Multiprotocol)	2 Gbps
(3DES/AES) VPN throughput	700 Mbps
IPsec site-to-site VPN peers	5000
VLANs	500
Concurrent firewall connections	1M
New connections per second	50K

Tabla 3.2: Características de equipamiento de Seguridad Perimetral.

3. Modifica letra a), punto N° 6 “Listado de Equipamiento” de las Especificaciones Técnicas

Donde dice:

Ítem	Código	Descripción	Cantidad
1	ASA5585-S20F20-K9	ASA 5585-X SSP-20, FirePOWER SSP-20,16GE,4GEMgt,1AC,3DES/AES	2
2	CAB-C2316-C19-IT	CEI 23-16 to IEC-C19 14ft Italy	4
3	ASA5585-PWR-AC	ASA 5585-X AC Power Supply	2
4	SF-ASA-X-9.2.2-K8	ASA 9.2.2 Software image for ASA 5500-X Series,5585-X,ASA-SM	2
5	ASA5585-20CTRL-LIC	Cisco ASA5585-20 Control License	2
6	ASA5585-BLANK-HD	ASA 5585-X Hard Drive Blank Slot Cover	4
7	ASA-SSP-20-INC	ASA 5585-X Security Services Processor-20 with 8GE	2
8	ASA5500-ENCR-K9	ASA 5500 Strong Encryption License (3DES/AES)	2
9	ASA5585-PWR-AC	ASA 5585-X AC Power Supply	2
10	ASA-SFR-20-INC-K9	ASA 5585-X FirePOWER SSP-20, 8GE	2
11	SF-ASA-FP5.4-K9	Cisco FirePOWER Software v5.4 for ASA 5500-X	2

Tabla 6: Listado de Equipamiento Solución Seguridad Perimetral

Debe decir:

Ítem	Código	Descripción	Cantidad
1	FPR2130-BUN	Cisco Firepower 2130 Master Bundle	1
2	FPR2130-NGFW-K9	Cisco Firepower 2130 NGFW Appliance, 1U, 1 x NetMod Bay	2
3	CON-PSRT-FPR2130W	PRTNR SS 8X5XNBD Cisco Firepower 2130 NGFW Appliance, 1U,	2
4	FPR2K-PWR-AC-400	Firepower 2000 Series 400W AC Power Supply	2
5	CAB-ACI	AC Power Cord (Italy), C13, CEI 23-16, 2.5m	4
6	SF-F2K-TD6.2.1-K9	Cisco Firepower Threat Defense software v6.2.1 for FPR2100	2
7	GLC-SX-MMD	1000BASE-SX SFP transceiver module, MMF, 850nm, DOM	4
8	FPR2K-SSD200	Firepower 2000 Series SSD for FPR-2130/2140	2
9	FPR2K-SLIDE-RAILS	Firepower 2000 Slide Rail Kit	2
10	FPR2K-FAN	Firepower 2000 Series Fan Tray	2
11	FPR2K-SSD-BBLKD	Firepower 2000 Series SSD Slot Carrier	2
12	FPR2K-NM-BLANK	Firepower 2000 Series Network Module Blank Slot Cover	2
13	FPR2K-PWR-AC-400	Firepower 2000 Series 400W AC Power Supply	2
14	L-FPR2130T-T=	Cisco FPR2130 Threat Defense Threat Protection License	2
15	L-FPR2130T-T-3Y	Cisco FPR2130 Threat Defense Threat Protection 3Y Subs	2
16	FS-VMW-2-SW-K9	Cisco Firepower Management Center,(VMWare) for 2 devices	2

Ítem	Código	Descripción	Cantidad
17	ASA5555-K9	ASA 5555-X with SW, 8GE Data, 1GE Mgmt, AC, 3DES/AES	2
18	CON-PSRT-A55K9	PRTNR SS 8X5XNBD ASA 5555-X with SW,	2
19	CAB-ACI	AC Power Cord (Italy), C13, CEI 23-16, 2.5m	2
20	ASA-PWR-AC	ASA 5545-X/5555-X AC Power Supply	2
21	SF-ASA-X-9.2.2-K8	ASA 9.2.2 Software image for ASA 5500-X Series,5585-X,ASA-SM	2
22	CAB-ACI	AC Power Cord (Italy), C13, CEI 23-16, 2.5m	2
23	ASA-HD-BLANK	ASA 5512-X -- 5555-X Hard Drive Blank Slot Cover	4
24	ASA-IC-C-BLANK	ASA 5545-X/5555-X Interface Card Blank Slot Cover	2
25	ASA5500-ENCR-K9	ASA 5500 Strong Encryption License (3DES/AES)	2
26	ASA5555-MB	ASA 5555 IPS Part Number with which PCB Serial is associated	2
27	ASA-PWR-AC	ASA 5545-X/5555-X AC Power Supply	2

Tabla 6: Listado de Equipamiento Solución Seguridad Perimetral